manual parking brake

ABOVEGROUND FUEL STORAGE AND ALARM SYSTEMS

pintle eye

25 Powers Drive, Meriden, CT 06451 Phone (800) 536-8910 Fax (203) 235-2749 www.safe-t-tank.com Email: us@safe-t-tank.com

NAME AND ADDRESS OF COMPANY REQUESTING QUOTATION:					
DESTINATION OF BOWSER:					
BOWSER/TRAILER RFQ DATA SHEET					
(Please mark or circle)					
<u>TANK</u>					
Tank gallons					
Steel	eel stainless steel				
5 gallon overfill prevention spill box (16" L x 12' W x 6" H) with debris screen and 2" pump out suction pipe					
<u>FUEL</u>					
Gasoline	JP8	JP-5	Jet A		
Diesel	Bio-diesel	used oil	other:		
TRAILER Vehicle being pulled by					
Street legal (fenders	, lights, running br	akes)	non-hi	ghway	
Smooth terrain			rough	terrain	
15 MPH (unsprung)		25 MPH (sprung)		55 MPH (sprung)	
straight frame (non-steering)		(160°) max. 15 MPH (5 th wheel steering under deck)			
pneumatic tires		soft ride solid tires (ground support equipment)			
(wheels under deck))				
fenders (wheels outboard)		lights			
electric brakes		hydraulic surge brakes		ball coupler	

wheel chocks



REFUEL (dispensing) pump 12 volt DC on board batteries single_____ dual GPM at nozzle _____ hose bin (for ≤25' hose length) hose reel (for ≥ 30 '+ of hose length) hose hook Feet of hose _____ Std 15 micron spin-on filter standard 2 micron spin-on filter Aviation 2 micron cartridge element filter **DEFUEL** (suction) pump 12 volt DC on board batteries single_____ dual____ Desired gallons per minute at hose end _____ Hose hook hose bin hose reel Feet of hose desired_____ Std 15 micron spin-on filter standard 2 micron spin-on filter

Email: us@safe-t-tank.com

Aviation 2 micron cartridge element filter

Pump & meter enclosed